



Technical data sheet AC0091HJBSMP32

Battery-powered hydraulic pressing tool

Contents

DESCRIPTION	3
TECHNICAL DATA	3

AC0091HJBSMP32

Battery-powered hydraulic pressing tool



DESCRIPTION

18 V pressing tool up to dimension 54/75 with 360° rotating pressing jaw holder and automatic piston return.

To be used for multilayer press fittings.

TECHNICAL DATA

DESCRIPTION	VALUES
Nominal force	32kN
Maximum lift	40mm
Maximum nominal size	110mm
Crimping time	approximately 4/7 sec (depending on DN))
Battery voltage	18 V DC
Battery capacity	3,0 Ah
Type of battery	Lithium ion
Charging time	approximately 60 min
Noise level	75 dB (A) at a distance of 1m
Acceleration	<2,5m/s ²
Hydraulic oil	Typ. "Shell-Tellus S2 V15"
Operating temperature	from -20°C to +40°C
Dimensions	374x334x82mm (including the power pack)
Weight	approximately 4,4kg (including the power pack)
Protection class	IP40
Conformity	CE



General Fittings Spa
Via Golgi, 73/75
25064 Gussago (BS) ITALY
Tel. +39 030 3739017
P.IVA 03448140172 - C.F. 01613110178
www.generalfittings.it