



Technical data sheet

Washing machine taps





DATA SHEFT

Contents

DESCRIPTION	3
FIELDS OF APPLICATION	3
COMPONENTS AND MATERIALS	3
REGULATIONS	4



WASHING MACHINE TAPS





DESCRIPTION

Chromed brass ball tap with washing machine connection for hot and cold water supply in plumbing and sanitary systems.

FIELDS OF APPLICATION

APPLICATIONS		T. min.	T. max	Max. pressure
0	drinking water	+5°C	+90°C	10 bar
	hot sanitary water	+5°C	+90°C	10 bar

COMPONENTS AND MATERIALS

COMPONENTS	MATERIALS
Stem	Brass CW617N - UNI EN 12164
Body	CW617N - UNI EN 12165 chromed
Ball	CW617N UNI-EN 12164 nickel plated
Stem O-Ring	Elastomer
Lever	ZAMAK
Ball O-Ring	Elastomer
Rosette	Stainless steel



REGULATIONS

- D.M. 174 (06/04/2004)
- Raw materials used are of high quality and comply with the Ministerial Decree N°174 dated 06/04/2004 concerning the materials and the items used in fixed installations for water collection, treatment and supply.
- UNI EN ISO 228-1:2003 Threads complies with UNI EN ISO 228-1:2003 law: "Piping thread for coupling not with thightness on the thread".
- Comply with 4MS, UBA List (BC group), DIN 50930/6 Dir. 2011/65/UE, 6C attachment III (RhOSII).









GENERAL FITTINGS SPA Via Golgi 73/75, 25064 Gussago (BS) - ITALY te. +39 030 3739017 www.generalfittings.it