MULTILAYER PIPE **SYSTEMS**

MULTILAYER PIPE **SYSTEMS**

FEATURES

Thanks to their peculiar characteristics, General Fittings multilayer pipe systems meet the various installation needs.

A wide and complete offer, consisting of 6 different ranges:

- Ewoprex: evolved DNA, the most complete press fittings
- Safe_press: the safest press fittings
- Trident: 3 in 1 press fittings
- 5S00: the multi-profile press fittings, available up to Ø63
- 5300: compression fittings with cut brass olive
- 5E00: compression fittings with removable pipe holder and cut brass olive

MKBROFL0002ENA





General Fittings Spa Via Golgi, 73/75 - 25064 Gussago (BS) ITALY T +39 030 3739017 - F +39 030 3739021 info@generalfittings.it

www.generalfittings.it











MULTILAYER PIPE SYSTEMS







EVOLVED DNA

Multi-profile press fittings with galvanic treatment and Leak Before Press system



- "Steel like tin" galvanic treatment: stable at ordinary high temperatures; reduces limescale deposits, protects against lead release, ensures high water potability, resists corrosion and wear, cancels dezincification, guarantees the permanence of lucidity over time
- + LEAK BEFORE PRESS function: if the fitting is not properly pressed, leaks are immediately noticed when the water circulates in the system
- Multitool: TH. H. U.
- Dielectric ring with window for checking the correct position of the pipe
- Colored ring for immediate identification of the diameter and thickness of the pipe
- + Available up to Ø63, including Ø16x2.25 and Ø20x2.50



LINE 5S00

Multijaws press fittings for multilayer pipe



- + Multitool: TH, H, U, B, F, CH
- + Dielectric ring with window for checking the correct position of the pipe
- DVGW approved
- Available up to Ø63

TRIDENT

Multijaws press fittings for

multilayer pipe for gas and water

3 in 1: WATER, GAS, HEATING

Certified O-Ring for water and gas

applications and dimensions Comply with UNI 11344 standards

position of the pipe

- Sleeve with colored stick for immediate identification of

Dielectric ring with window for checking the correct



- Both for drinking water and heating
- and water
- and the compression of the O-Ring of the pipe holder.



+ Seal guaranteed by the mechanical tightening of the fitting



- Compression fittings with cut olive
- Both for drinking water and heating
- DVGW approved

LINE 5300

+ No contact between nickel and water



MULTILAYER PIPE FOR WATER

MULTILAYER PIPE FOR GAS

TB00.20 Pe-xb/Al/Pe-xb in bar

TB00.20 Pe-xb/Al/Pe-xb in coils

TB00.20 Pe-xb/Al/Pe-xb

TB00.20 Pe-xb/Al/Pe-xb

TB00.20 Pe-xb/Al/Pe-xb

TB00.20 WHITE FRIO

white insulation

in coils with red insulation

in coils with blue insulation

in coils with grey insulation

Pe-xb/Al/Pe-xb in coils with

TB00.20.Y METALGAS BAR

Pe-xc/Al/Pe-xb in bar

TB00.20.Y METALGAS 2 Pe-x/Al/Pe-xb in coils

TB00.21.Y METALGAS 2

Corrugated yellow sheath

TB00.31.Y


Pe-xb/Al/Pe-xb in coils, with sheath

LINE 5F00

Compression fittings with removable pipe holder and cut olive







SAFE_PRESS

Multi-profile press fittings with Leak Before Press system



- LEAK BEFORE PRESS function: if the fitting is not properly pressed, leaks are immediately noticed when the water circulates in the system
- Multitool: TH. H. U
- Dielectric ring with window for checking the correct position of the pipe
- DVGW approved
- Available up to Ø63