



CERT

# DIN-DVGW type examination certificate

## DIN-DVGW-Baumusterprüfzertifikat

**NG-4502CO0460**

Registration Number  
Registriernummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	General Fittings s.r.l. Via Golgi, 73/75, I-25064 Gussago (BS)
<b>Distributor</b> <i>Vertreiber</i>	General Fittings s.r.l. Via Golgi, 73/75, I-25064 Gussago (BS)
<b>Product Category</b> <i>Produktart</i>	pipe equipment and fittings: separable unthreaded pipe connection for metal pipes (4502)
<b>Product Description</b> <i>Produktbezeichnung</i>	separable wedge fitting made of brass for pipes made of copper (R250) according to DVGW working sheet GW 392 with guaranteed tensile strength
<b>Model</b> <i>Modell</i>	1N00
<b>Test Reports</b> <i>Prüfberichte</i>	supplement test: 20140711 from 11.07.2014 (TTR)
<b>Test Basis</b> <i>Prüfgrundlagen</i>	DIN 3387-1 (01.11.2008)



770028-04-A-DE

**Date of Expiry / File No.** 20.12.2018 / 14-0351-GNR  
**Ablaufdatum / Aktenzeichen**

23.07.2014 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body  
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to EN 45011:1998 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN 45011:1998 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.



Deutsche  
Akkreditierungsstelle  
D-ZE-16028-01-01

DVGW CERT GmbH  
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3  
53123 Bonn

Tel. +49 228 91 88 - 888  
Fax +49 228 91 88 - 993

www.dvgw-cert.com  
info@dvgw-cert.com

<b>Type</b> <b>Typ</b>	<b>Technical Data</b> <b>Technische Daten</b>	<b>Remarks</b> <b>Bemerkungen</b>
1N00	pressure rating: MOP 5 nominal diameter: DN 12	
1N00	pressure rating: MOP 5 nominal diameter: DN 15	
1N00	pressure rating: MOP 5 nominal diameter: DN 18	
1N00	pressure rating: MOP 5 nominal diameter: DN 22	
1N00	pressure rating: MOP 5 nominal diameter: DN 28	

**Hints of Utilization / Remarks****Verwendungshinweise / Bemerkungen**

ambient temperature range: -20...+60 °C

connections: on all sides screw connection with clamp ring, on one side also thread according to DIN EN 10226-1