



GF PRO

PFOO.00

Film-Forming Anti-Algae
Protective Treatment

GF PRO - PF00.00 Film-Forming Anti-Algae Protective Treatment



GF PRO

DESCRIPTION

GF PRO is a film-forming anti-algae protective treatment specifically designed for underfloor heating and cooling systems.

FEATURES

GF PRO prevents scale build-up and corrosion while eliminating and inhibiting the formation of limescale, algae, and biological contaminants in heating and cooling systems, heat pumps, radiators, coils, heat exchangers, valves, and residential and industrial pipework.

It is particularly suitable for low-temperature systems and is compatible with all metals, including aluminium.

The product forms a continuous and uniform protective film on internal system surfaces, helping maintain system efficiency and extend service life.

APPLICATION

Flush and thoroughly rinse the system before treatment.

Add 1% GF PRO to the system to achieve a molybdenum concentration between 80 and 120 ppm.

Check the molybdenum level annually using the TEST KIT. If the concentration falls below 80 ppm, add an additional 1% dose of GF PRO.

STORAGE

Store in tightly sealed containers, protected from frost and direct sunlight.

AVVERTENZE

- H400: Very toxic to aquatic life.
- H411: Toxic to aquatic life with long lasting effects.
- P273: Avoid release to the environment.
- P391: Collect spillage.